TR Vent

TOTAL ROOF VENTING

Add ventilation underneath roofing and siding to extend the lifespan of your building.


TR Vent is a strong entangled polymer net product that creates a cutting-edge venting system under roofing and siding.

The unique design allows for the fastest installation of any rollable venting on the market. It can be rolled onto the roof or worksite table and cut to length very easily.

Enhancing ventilation underneath roofing and siding is an ideal way to eliminate the risk of condensation and increase the lifespan of your building.

Builder Benefits

- ► <u>HUGE SAVINGS!</u> There is no need to remove the old shingles when you apply TR Vent under your standing seam roof installation
- Wide roll size results in fewer seams
- Cuts with scissors & installs with staple hammer
- Promotes airflow and drainage
- Reduces environmental noise
- Meets most local codes
- Will not split, warp or rot
- Lightweight and easy to carry
- Provides no source for the promotion of mold, mildew or bacteria









TR Vent Technical Information

TOTAL ROOF VENTING

Product TR Vent

Thickness 0.30 inches 7.6 mm Length 50 feet 15.2 m


Width 48 inches 1,219.2 mm

Packing 1 Roll/Package 18 Rolls/Pallet 14 lbs (6.3 kg)/Roll

TR Vent Applications

- Standing Seam Metal Roofing
- Zinc Roofing
- Cedar Shake Roofing
- Siding Applications
- Other Applications:

 For more information on all roofing and siding applications, please contact our office.



This is just one of several great products we offer that can help make your installations easier, faster, and more cost effective. Ask about our complete line of building products.



CFB LLC Distributors

PO Box 308 Cornwall, PA USA 717-769-0857 office 717-222-5241 fax brian@cfbllcdistributors.com frank@cfbllcdistributors.com